## **EKONTAKT** simon



## TD1L.01/144

"Bell" push button with LED indicator light, champagne matt, 10AX

Series	Simon 55
Product name / Type	"Bell" push button with LED indicator light
Color	champagne matt
RAL (akin)	RAL 1035
Product type	Module
Nominal current	10 AX
Nominal voltage	250 V
Connection type / Crimp type	quick connection
IP degree of protection	IP20/IP44
Notes	To obtain IP44 splash-proof class an additional frame seal required, Photo for illustration purposes only. Product's mounting frame is also available in a black, galvanized version. Different color results from the continuous development of Kontakt-Simon products.
Backlight,	Built-in, Orientated, Replaceable LED, color: white

ETIM Class EC000029 Push button  In print/Pictogram symbol "bell"  Type of material Plastic, Halogen free  Surface protection varnished  Type of curface matt  Mounting flush mounted  Fixing method claws / screws  Height of product 75 mm  Depth of product 39.5 mm  Installation depth 26 mm  Operating method / Way of operating  Number of buttons / levers  Connection layout Single push button  Number of poles 1  Connectors - operating Single normally open connector		
Type of material Plastic, Halogen free  Surface protection varnished  Type of curface matt  Mounting flush mounted  Fixing method claws / screws  Height of product 75 mm  Width of product 75 mm  Depth of product 39.5 mm  Installation depth 26 mm  Operating method / Way of operating  Number of buttons / levers  Connection layout Single button  Model Single push button  Number of poles 1  Connectors - operating Single normally open connector	ETIM Class	EC000029 Push button
Halogen free  Surface protection varnished  Type of curface matt  Mounting flush mounted  Fixing method claws / screws  Height of product 75 mm  Width of product 75 mm  Depth of product 39.5 mm  Installation depth 26 mm  Operating method / way of operating  Number of buttons / levers  Connection layout Single button  Number of poles 1  Connectors - operating Single normally open connector	In print/Pictogram	symbol "bell"
Type of curface matt  Mounting flush mounted method[ETIM] flush mounted  Fixing method claws / screws  Height of product 75 mm  Width of product 75 mm  Depth of product 39.5 mm  Installation depth 26 mm  Operating method / Way of operating  Number of buttons / levers  Connection layout Single button  Model Single push button  Number of poles 1  Connectors - operating Single normally open connector	Type of material	
Mounting method [ETIM]  Fixing method claws / screws  Height of product 75 mm  Width of product 39.5 mm  Installation depth 26 mm  Operating method / Way of operating  Number of buttons / levers  Connection layout Single button  Model Single push button  Number of poles 1  Connectors - operating Single normally open connector	Surface protection	varnished
method[ETIM]  Fixing method claws / screws  Height of product 75 mm  Width of product 75 mm  Depth of product 39.5 mm  Installation depth 26 mm  Operating method / Way of operating  Number of buttons / levers  Connection layout Single button  Model Single push button  Number of poles 1  Connectors - operating Single normally open connector	Type of curface	matt
Height of product 75 mm  Width of product 75 mm  Depth of product 39.5 mm  Installation depth 26 mm  Operating method / way of operating  Number of buttons / 1  Connection layout Single button  Model Single push button  Number of poles 1  Connectors - operating Single normally open connector		flush mounted
Width of product 75 mm  Depth of product 39.5 mm  Installation depth 26 mm  Operating method / Way of operating  Number of buttons / levers  Connection layout Single button  Model Single push button  Number of poles 1  Connectors - operating Single normally open connector	Fixing method	claws / screws
Depth of product 39.5 mm  Installation depth 26 mm  Operating method / rocker button  Number of buttons / 1  Installation depth 26 mm  Operating method / rocker button  Number of buttons / 1  Installation depth 26 mm  Single button  Number of buttons / 1  Single push button  Number of poles 1  Connectors - operating Single normally open connector	Height of product	75 mm
Installation depth 26 mm  Operating method / Way of operating  Number of buttons / levers  Connection layout Single button  Model Single push button  Number of poles 1  Connectors - operating Single normally open connector	Width of product	75 mm
Operating method / rocker button Way of operating  Number of buttons / 1 levers  Connection layout  Single button  Model  Single push button  Number of poles  1  Connectors - operating  Single normally open connector	Depth of product	39.5 mm
Way of operating  Number of buttons / 1 levers  Connection layout Single button  Model Single push button  Number of poles 1  Connectors - operating Single normally open connector	Installation depth	26 mm
levers  Connection layout Single button  Model Single push button  Number of poles 1  Connectors - operating Single normally open connector		rocker button
Model Single push button  Number of poles 1  Connectors - operating Single normally open connector		1
Number of poles 1  Connectors - operating Single normally open connector	Connection layout	Single button
Connectors - operating Single normally open connector	Model	Single push button
	Number of poles	1
(NO)	Connectors - operating	Single normally open connector (NO)

Outer carton quantity	10
Measure unit	Qty.
Individual packaging EAN code	5902787888732
Pack. type	foil
Ind. pack. height	16 cm
Ind. pack. width	11 cm
Individual packaging lenght	4.5 cm
Weight of individual packaging with product	0.06 kg
Outer type	cardboard box
Height of outer	10 cm
Outer width	19 cm
Outer lenght	23 cm