



## SWITCHBOXD

WITHDRAWN FROM OFFER, Replacement: EW2W, controller for devices and lighting 2x5A [Wi-Fi]

|                                |   |                   |  |                               |               |
|--------------------------------|---|-------------------|--|-------------------------------|---------------|
| Status of Product              | WITHDRAWN FROM OFFER  | Type of material  | Halogen-free, self-extinguishing polyurethane - Class B                                  | Outer carton quantity         | 18            |
| Series                         | Simon GO  | Number of outputs | 1  | Measure unit                  | Qty.          |
| Product name / Type            | controller for devices and lighting 2x5A [Wi-Fi]  | Fixing            | Installation in a recessed mounting box, in the receiver housing, At the top of the post | Individual packaging EAN code | 5900168580091 |
| Product type                   | flush-mounted controller  |                   |  | Pack. type                    | carton        |
| IP degree of protection        | IP20  |                   |  | Ind. pack. height             | 53 cm         |
| Energy consumption             | < 1 W   |                   |  | Ind. pack. width              | 30 cm         |
| Communication standard         | IEEE 802.11b/g/n (20 MHz), Compatible with WiFi, µWiFi  |                   |  | Individual packaging length   | 40 cm         |
| Type of transmission           | two-way, Encrypted, with confirmation   |                   |  | Outer EAN13                   | 5900168580091 |
| Transmission frequency         | 2.4-2.4 GHz   |                   |  | Maximum current (per channel) | 16 A          |
| Compatible devices and systems | Android, Apple iPad, Apple iPhone, iPad Mini, HTML5-compatible computers and mobile devices                                     |                   |  |                               |               |
| Controlled via application     | SimonGO   |                   |  |                               |               |
| Maximum load                   | 3500 W  |                   |  |                               |               |
| Operating mode                 | Wi-Fi connection through a standard router, Direct connection, Connection from anywhere in the world (internet access required) |                   |  |                               |               |
| Current                        | 230 V   |                   |  |                               |               |
| type of outputs                | relay   |                   |  |                               |               |
| Voltage                        | 230 V   |                   |  |                               |               |
| Number of inputs               | 1   |                   |  |                               |               |
| Supported push-buttons         | Bistable (traditional, cross) - without backlight, Monostable (bell-type)   |                   |  |                               |               |
| Type of inputs                 | Configurable, logical, Button-based, neutral (N) connection   |                   |  |                               |               |
| Maximum total current          | 16 A  |                   |  |                               |               |
| Replacement                    | EW2W  |                   |  |                               |               |